




For the latest data sheet, please visit [www.sunnywale.com](http://www.sunnywale.com)



## IMX294CJK

Diagonal 21.63 mm (Type 4/3) Approx. 10.71M-Effective Pixel  
Color CMOS Image Sensor

### High-Sensitivity Type 4/3 CMOS Image Sensor that Supports 4K for Security Camera and Industrial Applications

Sony Semiconductor Solutions Corporation has commercialized the "IMX294CJK" Type 4/3 back-illuminated CMOS image sensor with approximately 10.71M-effective pixels for the expanding security camera market.

The "IMX294CJK" is the first in-house image sensor for security cameras to adopt the Type 4/3 format, and realizes output of the number of pixels needed for 4K at 120 frame/s (in ADC

10-bit output mode). In addition, use of a large-size pixel achieves SNR1s of 0.14 lx<sup>\*1</sup>, and use of a Quad Bayer pixel structure (see Figure 1) realizes an HDR (High Dynamic Range) function with no time difference, enabling video imaging with a wide dynamic range.

<sup>\*1</sup>: Low illuminance performance index advocated by Sony for image sensors for industrial applications

- Large-size optical format (Type 4/3)
- Supports 4K output at 120 frame/s
- High sensitivity (SNR1s = 0.14 lx)
- High-speed interfaces (CSI-2/SLVS-EC<sup>\*2</sup>)
- Supports Quad Bayer Coding HDR

<sup>\*2</sup>: Scalable Low Voltage Signaling Embedded Clock

#### Exmor R

<sup>\*</sup> Exmor R is a registered trademark or trademark of Sony Group Corporation or its affiliates. The Exmor R is a Sony's CMOS image sensor with significantly enhanced imaging characteristics including sensitivity and low noise by changing fundamental structure of Exmor™ pixel adopted column parallel A/D converter to back-illuminated type.

#### STARVIS

<sup>\*</sup> STARVIS is a registered trademark or trademark of Sony Group Corporation or its affiliates. The STARVIS is back-illuminated pixel technology used in CMOS image sensors for security camera applications. It features a sensitivity of 2000 mV or more per 1 μm<sup>2</sup> (color product, when imaging with a 706 cd/m<sup>2</sup> light source, F5.6 in 1 s accumulation equivalent), and realizes high picture quality in the visible-light and near infrared light regions.

### Supports Type 4/3 4K output

The IMX294CJK adopts Type 4/3 as the optical size, and supports various output formats (angle of view) including 10M (3704 × 2778) for aspect ratio 4:3, UHD (3840 × 2160)

for 16:9, and 4096 × 2160 for 17:9. In addition, the A/D converter can be selected from 10 bits, 12 bits, and 14 bits according to the application (Table 3).

### Exceptional low-illumination performance

Exceptional low-illumination performance of SNR1s: 0.14 lx is realized by use of a large-size optical system and by expanding the area per pixel to 4.63 μm. This makes the IMX294CJK

ideal for security camera market applications that require low-illumination performance (Photograph 2).

### High-speed movie imaging

This product realizes high-speed movie imaging with a 4K angle of view at the high frame rate of 120 frame/s, and also enables high-speed imaging at 60 frame/s in HDR drive mode.

In addition, use of our proprietary high-speed serial interface


SLVS-EC together with high-speed imaging enables image transfer with few signal lines. This product is also equipped with a general-purpose MIPI (CSI-2) interface, and supports connection with a general-purpose ISP (Image Signal Processor).

### Quad Bayer Coding HDR

The IMX294CJK uses a Quad Bayer structure, and outputs data binned in 2 × 2 pixel units in normal mode. In HDR mode, integration can be divided into long-time integration and short-time integration for each 2 pixels in the Quad array

(Figure 1). In this case there is no time difference between long-time integration and short-time integration, which realizes HDR with little blending offset when imaging moving subjects (Photograph 3).

<Figure 1> CFA Structure



<Photograph 1> Normal image

Condition: 500 lx F2.0 (Exposure time 33.3 ms, Internal gain 0 dB)



<Photograph 2> Low illumination image

Condition: 0.2 lx F2.0 (Exposure time 33.3 ms, Internal gain 45 dB (HCG))



<Photograph 3> Example of HDR image

Condition: Exposure time (3.2 ms/0.2 ms) blended image



Multiple exposure HDR



Quad Bayer Coding HDR

<Table 1> Device Structure

Item		IMX294CJK	
Output image size		Diagonal 21.63 mm (Type 4/3) aspect ratio 17:9 & 4:3	
Number of effective pixels		4168 (H) × 2176 (V) approx. 8.93M pixels (aspect ratio 17:9) / 3792 (H) × 2824 (V) approx. 10.71M pixels (aspect ratio 4:3)	
Unit cell size		4.63 μm (H) × 4.63 μm (V)	
Optical blacks	Horizontal	Front: 0 pixels, rear: 0 pixels	
	Vertical	Front: 16 pixels, rear: 0 pixels	
Input drive frequency		72 MHz (SLVS-EC) / 6 to 27 MHz (MIPI CSI-2)	
Output Interface		SLVS-EC (2.304 Gbps / Lane) Max. 8lane / MIPI CSI-2 (1.728 Gbps / Lane) Max. 4lane	
Package		248-pin LGA	
Supply voltage VDD (Typ.)		2.8 V / 1.8 V / 1.2 V	

<Table 2> Image Sensor Characteristics

Item		Value	Remarks
Sensitivity (F5.6)	Typ.	1900 mV	1/30s accumulation (HCG)
Saturation signal	Min.	970 mV	Tj = 60 °C (LCG)

<Table 3> Basic Drive Mode

Drive mode	Recommended number of recording pixels	Frame rate [frame/s]	ADC [bit]
All-pixel scan (aspect ratio 4:3)	3704 (H) × 2778 (V)	24	14
All-pixel scan (aspect ratio 17:9)	4096 (H) × 2160 (V)	60 (SLVS-EC) / 30 (CSI-2)	12
All-pixel scan (aspect ratio 16:9)	3840 (H) × 2160 (V)	60 (CSI-2)	12
All-pixel scan (aspect ratio 4:3)	3704 (H) × 2778 (V)	60 (SLVS-EC) / 30 (CSI-2)	12
All-pixel scan (aspect ratio 17:9) Horizontal/vertical 2/2-line binning	2048 (H) × 1080 (V)	120 (SLVS-EC) / 60 (CSI-2)	12
All-pixel scan (aspect ratio 17:9)	4096 (H) × 2160 (V)	120 (SLVS-EC) / 60 (CSI-2)	10
HDR-1 (aspect ratio 17:9)	4096 (H) × 2160 (V)	60 (SLVS-EC) / 30 (CSI-2)	10
HDR-2 (aspect ratio 4:3)	3704 (H) × 2778 (V)	30 (SLVS-EC) / 15 (CSI-2)	10
HDR-3 (aspect ratio 17:9) Horizontal/vertical 2/2-line binning	2048 (H) × 1080 (V)	60	10

Sony reserves the right to change products and specifications without prior notice.  
"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.